


12 V								MH
til. no	(MC-Japan nr)	Ah	Alv 22%	pit.	lev.	kork.	navoitus	
04575	YB2,5L-C2	2,5	24	81	71	106	3	
04543	YB3L-A	3	26	99	57	111	3	
04545	YB3L-B	3	26	99	57	111	3	
04516	YB4L-B	4	30	121	71	93	3	
04961	YB4L-A	4	30	121	71	93	3	
04517	12N5-3B	5	32	121	61	131	3	
04546	YB5L-B	5	33	121	61	131	3	
04518	12N5,5A-3B	5,5	38	103	90	114	3	
04550	12N5,5-4A	5,5	38	145	60	130	4	
04559	12N5,5-3B	5,5	40	138	61	131	3	
04560	12N7-3B	7	42	137	76	134	3	
04928	12N7-4B	7	42	137	76	134	4	
04536	YB7C-A	8	50	130	90	114	3	
04577	YB7-A	8	50	137	76	134	4	
04583	YB7L-B	8	50	137	76	134	3	
04503	12N9-4B-1	9	45	137	76	140	4	
04554	YB9L-B	9	48	137	76	140	3	
04573	12N9-3B	9	47	137	76	140	3	
04581	YB9L-A2	9	48	137	76	140	3	
04980	YB9B	9	48	137	76	140	4	
04526	YB10L-A2	11	49	136	91	146	3	
04562	YB10L-B.	11	50	136	91	146	3	
04967	YB10L-B2	11	49	136	91	146	3	
04520	12N12A-4A-1	12	44	135	81	161	4	
04525	YB12A-A	12	52	135	81	161	4	
04563	YB12A-B	12	52	135	81	161	4	
04564	YB12AL-A	12	52	135	81	161	3	
04565	YB12B-B2	12	60	161	91	132	4	
04579	YB12AL-A2	12	56	135	81	161	3	
04968	YB12C-A	12	56	135	81	175	4	
04521	12N14-3A	14	48	135	90	167	3	
04527	YB14-A2	14	60	135	91	167	4	
04529	YB14L-A2	14	60	135	91	167	3	
04566	YB14-B2	14	60	135	91	167	4	
04567	YB14L-B2	14	60	135	91	167	3	

Napojen sijainti :



Tuuletus:



til. no	(MC-Japan nr)	Ah	Alv 22%	pit.	lev.	kork.	navoitus
04530	YB16AL-A2	16	65	205	71	164	3
04569	HYB16A-A	16	65	151	91	182	4

04985	YB16B-A1	16	68	162	92	162	4
04531	YB18L-A	18	72	182	92	164	3
04555	12Y16A-3B	18	89	196	82	172	3
04570	12N18-3	18	77	206	91	164	3
04532	YB16B-A	19	70	162	92	162	4
04533	YB16B	19	70	176	101	156	4
04534	YB16L-B	19	70	176	101	156	3
04574	YB16CL-B	19	78	173	100	175	3
04997	12Y16-3A	19	98	181	77	167	3
04528	Y50-N18L-A2	20	82	206	91	164	3
04572	Y50-N18L-A3	20	82	206	91	160	3
04501	12N24-3A	24	68	186	125	176	3
04523	12N-24-4A	24	68	186	125	176	4
04934	U1-9	24	92	196	131	184	4
04935	U1-R9	24	92	196	131	184	3
04522	Y60-N24L-A	28	105	185	125	176	3
04538	Y60-N24AL-B	28	105	185	125	176	3
04580	B68-12	28	98	185	125	176	4
04925	YHD4-12	28	108	205	130	165	4
04582	Y60N30L-A	30	120	187	130	170	3
04987	YB30L-B	30	125	168	132	176	3
04998	Y60-N30L-B	30	130	185	128	168	3

6 V							
til. no	(MC-Japan nr)	Ah	Alv 22%	pit.	lev.	kork.	navoitus
04504	6N4-2A	2	17	71	71	96	2
04514	6N4B-2A	4	18	103	48	96	2
04515	6N4A-4D	4	18	58	62	131	6
04556	6N4-2A-7	4	17	71	71	96	1
04557	6N4-2A-4	4	17	71	71	96	3
04506	6N6-3B-1	6	20	108	56	110	3
04548	6N6-1D-2	6	20	99	57	111	1
04505	B39-6 (6N7-1)	7	30	126	48	126	1
04507	B49-6	8	32	91	83	161	2
04542	6N11A-1B	11	32	122	62	132	1
04558	6N12A-2D	12	32	156	57	116	2
04513	B38-6A	14	39	129	83	162	1

Napojen sijainti :



Tuuletus:



12 V YTX akut (happopatruunat mukana)							
til. no	(MC-Japan nr)	Ah	Alv 22%	pit.	lev.	kork.	navoitus
04992	YT4B-BS	2,3	44	113	38	85	5
04972	YTR4A-BS	2,3	50	114	49	86	5
04590	YT4L-BS	3	42	114	71	86	3
04592	YTX5L-BS	4	47	114	71	106	3
04593	YTX7A-BS	6	55	114	88	94	4
04975	YTZ7-BS	6	67	113	70	105	3

04594	YTX7L-BS	6	55	114	71	131	3
04903	YT9B-BS	8	82	150	69	105	4
04595	YTX9-BS	8	64	152	88	106	4
04962	YTX9C-BS	9	58	135	75	136	4
04905	YT12A-BS	9,5	99	152	88	106	4
04596	YTX12-BS	10	70	152	88	131	4
04906	YT12B-BS	10	105	150	69	130	4
04977	YTZ12S-BS	11	102	150	87	110	4
04597	YTX14-BS	12	80	152	88	147	4
04995	YTX14AH-BS	12	102	134	89	166	4
04907	YT14B-BS	12	137	152	70	147	4
04996	YTX14AHL-BS	12	102	134	89	166	3
04991	YTX15L-BS	13	95	175	87	130	3
04974	YTX16-BS	14	100	152	88	163	4
04598	YTX20-BS	18	105	175	86	154	4
04599	YTX20L-BS	18	105	175	86	154	3
04999	YTX20CH-BS	18	127	150	87	161	4
04994	YTX24HL-BS	21	130	205	87	162	3

#### 12 V SULJETUT AKUT

til. no	(MC-Japan nr)	Ah	Alv 22%	pit.	lev.	kork.	navoitus
04584	SLA12-18	18	115	180	75	165	3
04990	YIX30L	30	136	170	130	175	3
800191	GEL.G19	19	249	186	82	174	3

**Exide Technologies Oy**